



Figure similar

Article No. : 1FK7033-4CF21-1BA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data      |             |
|-----------------------|-------------|
| Rated speed (100 K)   | 3,000 rpm   |
| Number of poles       | 6           |
| Rated torque (100 K)  | 1.2 Nm      |
| Rated current         | 2.0 A       |
| Static torque (60 K)  | 1.08 Nm     |
| Static torque (100 K) | 1.30 Nm     |
| Stall current (60 K)  | 1.70 A      |
| Stall current (100 K) | 2.10 A      |
| Moment of inertia     | 0.250 kgcm² |
| Efficiency            | 86.0 %      |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 0.62 Nm/A                     |
| Voltage constant at 20° C   | 39.5 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 3.51 Ω                        |
| Rotating field inductance   | 22.0 mH                       |
| Electrical time constant    | 6.30 ms                       |
| Mechanical time constant    | 0.68 ms                       |
| Thermal time constant       | 25 min                        |
| Shaft torsional stiffness   | 7,300 Nm/rad                  |
| Net weight of the motor     | 3.0 kg                        |

| Mechanical data          |                                                       |
|--------------------------|-------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                    |
| Motor type               | High Dynamic                                          |
| Shaft height             | 36                                                    |
| Cooling                  | Natural cooling                                       |
| Radial runout tolerance  | 0.035 mm                                              |
| Concentricity tolerance  | 0.08 mm                                               |
| Axial runout tolerance   | 0.08 mm                                               |
| Vibration severity grade | Grade A                                               |
| Connector size           | M23                                                   |
| Degree of protection     | IP64                                                  |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                  |
| Temperature monitoring   | Pt1000 temperature sensor                             |
| Electrical connectors    | Connectors for signals and power rotatable            |
| Color of the housing     | Standard (Anthracite RAL 7016)                        |
| Holding brake            | without holding brake                                 |
| Shaft end                | Feather key                                           |
| Encoder system           | Encoder AS24DQI: absolute encoder single-turn 24 bits |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 3,000 rpm |
| Optimum power           | 0.4 kW    |

| Limiting data                     |            |
|-----------------------------------|------------|
| Max. permissible speed (mech.)    | 10,000 rpm |
| Max. permissible speed (inverter) | 7,150 rpm  |
| Maximum torque                    | 4.3 Nm     |
| Maximum current                   | 7.6 A      |

| Recommended Motor Module |         |
|--------------------------|---------|
| Rated inverter current   | 2 A     |
| Maximum inverter current | 5 A     |
| Maximum torque           | 2.70 Nm |