SIEMENS

## Data sheet for SIMOTICS S-1FK7

**Article No. :** **1FK7061-4CH71-1CG1**

Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | |
|---|---|
| Rated speed (100 K) | 4,500 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 4.3 Nm |
| Rated current | 6.2 A |
| Static torque (60 K) | 5.30 Nm |
| Static torque (100 K) | 6.40 Nm |
| Stall current (60 K) | 7.10 A |
| Stall current (100 K) | 8.70 A |
| Moment of inertia | 4.100 kgcm² |
| Efficiency | 93.0 % |

| Physical constants | |
|---|---|
| Torque constant | 0.73 Nm/A |
| Voltage constant at 20° C | 47.0 V/1000*min⁻¹ |
| Winding resistance at 20° C | 0.35 Ω |
| Rotating field inductance | 10.7 mH |
| Electrical time constant | 30.50 ms |
| Mechanical time constant | 0.79 ms |
| Thermal time constant | 45 min |
| Shaft torsional stiffness | 36,500 Nm/rad |
| Net weight of the motor | 9.5 kg |

| Mechanical data | |
|---|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | High Dynamic |
| Shaft height | 63 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.10 mm |
| Axial runout tolerance | 0.10 mm |
| Vibration severity grade | Grade A |
| Connector size | M23 |
| Degree of protection | IP65 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | Pt1000 temperature sensor |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | Standard (Anthracite RAL 7016) |
| Holding brake | without holding brake |
| Shaft end | Plain shaft |
| Encoder system | Encoder AM24DQI: absolute encoder 24 bits (resolution 16777216, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |

| Optimum operating point | |
|---|---|
| Optimum speed | 4,500 rpm |
| Optimum power | 2.0 kW |

| Limiting data | |
|---|---|
| Max. permissible speed (mech.) | 7,500 rpm |
| Max. permissible speed (inverter) | 7,500 rpm |
| Maximum torque | 17.3 Nm |
| Maximum current | 26.5 A |

| Recommended Motor Module | |
|---|---|
| Rated inverter current | 9 A |
| Maximum inverter current | 27 A |
| Maximum torque | 17.30 Nm |