



Figure similar

SIPLUS S7-1200 CM 1243-2 based on 3RK7243-2AA30-0XB0 with conformal coating, -25...+70 °C, S7-1200, CM 1243-2 communications module AS-Interface master according to AS-i specification V3.0

General technical data		
product designation		SIPLUS AS-Interface master
product type designation		CM 1243-2
protection class IP		IP20
type of electrical connection of the AS-Interface		Screw-type connection
type of voltage supply		via backplane bus
consumed current		
• from profile conductors of the AS-Interface		
— at 30 V maximum	mA	100
• from backplane bus maximum	mA	250
power loss [W]	W	2.9
insulation voltage rated value	V	500
product feature redundancy capability		No
product function suitable for AS-i Power24V		Yes
• note		All product versions
display version		
• as status display by LED		AS-i, PF, CM, CER, DIAG
type of configuration of the AS-Interface		With STEP7, command interface
Communication/ Protocol		
version of the AS-Interface specification		V 3.0
AS-Interface master profile is supported		M4 (in acc. with AS-interface specification V 3.0)
type of data transmission		S7-1200 backplane bus
number of units per CPU maximum		3
number of units per CPU maximum note		Max. 3 communication modules in total (CM /CP)
number of interfaces		
• as AS-Interface		1
• according to USB		0
protocol is supported		
• TCP/IP		No
Inputs/ Outputs		
number of inputs for AS-Interface maximum		496
number of outputs for AS-Interface maximum		496
number of AS-i devices per AS-Interface maximum		62
access to digital I/O data		via process image/peripheral addresses
access to analog I/O data		via process diagram/peripheral addresses and data record transfer
Mechanical data		
fastening method		snap-on fastening on 35 mm DIN rail

module format		S7-1200 design
Ambient conditions		
ambient temperature		
• if installed on horizontal mounting rail during operation	°C	0 ... 55
• if installed on vertical mounting rail during operation	°C	-25 ... +70
installation altitude at height above sea level maximum	m	2 000
Safety related data		
explosion protection marking for intrinsic safety of related equipment		
• EEx ia		No
• EEx ib		No
explosion protection category for gas		none
explosion protection category for dust		none
Certificates/ approvals		
General Product Approval		



[Manufacturer Declaration](#)



[China RoHS](#)



[China RoHS](#)

General Product Approval	For use in hazardous locations
   	

Further information
Information on the packaging https://www.modulplc.com/?s=6AG1243-2AA30-7XB0
Information for data generation and storage https://www.modulplc.com/?s=6AG1243-2AA30-7XB0
Information- and Downloadcenter (Catalogs, Brochures,...) https://www.modulplc.com/?s=6AG1243-2AA30-7XB0
Industry Mall (Online ordering system) https://www.modulplc.com/?s=6AG1243-2AA30-7XB0
Cax online generator https://www.modulplc.com/?s=6AG1243-2AA30-7XB0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://www.modulplc.com/?s=6AG1243-2AA30-7XB0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) https://www.modulplc.com/?s=6AG1243-2AA30-7XB0

last modified:

4/17/2025 