



Figure similar

spare part SIPLUS S7-300 CP 340 RS-422/485 based on 6ES7340-1CH02-0AE0 with conformal coating, -25...+60 °C, communications processor with RS-422/485 interface incl. configuration package on CD-ROM

General information	
based on	6ES7340-1CH02-0AE0
Supply voltage	
Rated value (DC)	
• 24 V DC	No; Power supply via backplane bus 5V
Input current	
from backplane bus 5 V DC, max.	165 mA
Power loss	
Power loss, typ.	0.6 W
Power loss, max.	0.85 W
Interfaces	
Interfaces/bus type	RS 422 / 485 (X.27)
Number of interfaces	1; Isolated
Transmission rate, min.	2.4 kbit/s
Transmission rate, max.	19.2 kbit/s
Point-to-point connection	
• Cable length, max.	1 200 m
• supported printers	HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined
• Connector type	15-pin sub D socket
Integrated protocol driver	
— 3964 (R)	Yes
— ASCII	Yes
— RK 512	No
— customer-specific drivers reloadable	No
Telegram length, max.	
— 3964 (R)	1 024 byte
— ASCII	1 024 byte
Transmission rate, RS 422/485	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	9.6 kbit/s
— with printer driver, max.	9.6 kbit/s
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Receive RxD	Yes
• Transmit TxD	Yes
• Group error SF (red)	Yes
Standards, approvals, certificates	
CE mark	Yes

UL approval	Yes; File E239877		
RCM (formerly C-TICK)	Yes		
KC approval	Yes		
EAC (formerly Gost-R)	Yes		
Ambient conditions			
Ambient temperature during operation			
<ul style="list-style-type: none">min.	-25 °C; = Tmin		
<ul style="list-style-type: none">max.	60 °C; = Tmax		
Ambient temperature during storage/transportation			
<ul style="list-style-type: none">min.	-40 °C		
<ul style="list-style-type: none">max.	70 °C		
Altitude during operation relating to sea level			
<ul style="list-style-type: none">Installation altitude above sea level, max.	5 000 m		
<ul style="list-style-type: none">Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)		
Relative humidity			
<ul style="list-style-type: none">With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)		
Resistance			
Use in stationary industrial systems			
<ul style="list-style-type: none">— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request		
<ul style="list-style-type: none">— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *		
<ul style="list-style-type: none">— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *		
Use on ships/at sea			
<ul style="list-style-type: none">— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request		
<ul style="list-style-type: none">— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *		
<ul style="list-style-type: none">— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *		
Usage in industrial process technology			
<ul style="list-style-type: none">— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)		
<ul style="list-style-type: none">— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)		
Remark			
<ul style="list-style-type: none">Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!		
Software			
Block			
<ul style="list-style-type: none">FB length in RAM, max.	2 700 byte; Data communication, sending and receiving		
Connection method			
Design of electrical connection for supply voltage	Over backplane bus		
Dimensions			
Width	40 mm		
Height	125 mm		
Depth	120 mm		
Weights			
Weight, approx.	300 g		
Classifications			
		Version	Classification
	eClass	16	27-24-22-08
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08

eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



EG-Konf.

[Manufacturer Declaration](#)



[China RoHS](#)



UL



EMV

For use in hazardous locations





RCM



IECEx



ATEX

[CCC-Ex](#)

last modified:

12/8/2024 