

product type designation



Figure similar

CP 342-5

spare part SIPLUS NET CP 342-5 PROFIBUS based on 6GK7342-5DA03-0XE0 with conformal coating, -25...+70 °C, communications processor CP 342-5 for connecting SIMATIC S7-300 to PROFIBUS, DP, S5-compatible, PG/OP and S7 communication

product brand name

SIPLUS

Technical Product Detail Page

<https://www.modulplc.com/?s=6AG1342-5DA03-7XE0>

transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

interfaces

number of interfaces / according to Industrial Ethernet

0

number of electrical connections

- at the 1st interface / according to PROFIBUS
- for power supply

1

1

type of electrical connection

- at the 1st interface / according to PROFIBUS
- for power supply

9-pin Sub-D socket (RS485)

4-pole terminal block

supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage / 1 / from backplane bus

5 V

supply voltage / external

24 V

relative positive tolerance / at DC / at 24 V

20 %

relative negative tolerance / at DC / at 24 V

15 %

consumed current

- from backplane bus / at DC / at 5 V / typical
- from external supply voltage / at DC / at 24 V / typical

0.15 A

0.25 A

power loss [W]

6.75 W

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-25 ... +70 °C

-40 ... +70 °C

-40 ... +70 °C

installation altitude / at height above sea level / maximum

5000 m

ambient condition / relating to ambient temperature - air pressure - installation altitude

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

relative humidity

- with condensation / according to IEC 60068-2-38 / maximum

100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation

chemical resistance / to commercially available cooling lubricants

Yes; incl. airborne diesel and oil droplets

resistance to biologically active substances

<ul style="list-style-type: none"> conformity according to EN 60721-3-3 	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
<ul style="list-style-type: none"> conformity according to EN 60721-3-6 	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
<ul style="list-style-type: none"> conformity according to EN 60721-3-3 	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
<ul style="list-style-type: none"> conformity according to EN 60721-3-6 	Yes
resistance to mechanically active substances	
<ul style="list-style-type: none"> conformity according to EN 60721-3-3 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
<ul style="list-style-type: none"> conformity according to EN 60721-3-6 	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.3 kg
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> per CPU / maximum 	4
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
data volume	
<ul style="list-style-type: none"> as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	240 byte
performance data / PROFIBUS DP	
service / as DP master	
<ul style="list-style-type: none"> DPV0 	Yes
number of DP devices	
<ul style="list-style-type: none"> on DP master / operable 	124
data volume	
<ul style="list-style-type: none"> of the address range of the inputs / as DP master / total 	2160 byte
<ul style="list-style-type: none"> of the address range of the outputs / as DP master / total 	2160 byte
<ul style="list-style-type: none"> of the address range of the inputs / per DP device 	244 byte
<ul style="list-style-type: none"> of the address range of the outputs / per DP device 	244 byte
<ul style="list-style-type: none"> of the address range of the diagnostic data / per DP device 	240 byte
service / as DP device	
<ul style="list-style-type: none"> DPV0 	Yes
data volume	
<ul style="list-style-type: none"> of the address range of the inputs / as DP device / total 	240 byte
<ul style="list-style-type: none"> of the address range of the outputs / as DP device / total 	240 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	16
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> without DP / maximum 	32
<ul style="list-style-type: none"> with DP / maximum 	28
performance data / telecontrol	

protocol / is supported	No	
product functions / management, configuration, engineering		
configuration software	STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher	
• required		
further information / internet links		
internet link	<div><ul style="list-style-type: none">• to website: Selection guide for cables and connectors• to web page: selection aid TIA Selection Tool• to website: Industrial communication• to web page: SiePortal• to website: Image database• to website: CAX-Download-Manager• to website: Industry Online Support</div> <div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div><div>https://www.modulplc.com/?s=6AG1342-5DA03-7XE0</div></div>	
security information		
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.modulplc.com/?s=6AG1342-5DA03-7XE0 (V4.7)</p>	
Approvals / Certificates		
General Product Approval		
<div><div><div> EG-Konf.</div><div>Manufacturer Declaration</div><div></div><div>China RoHS</div><div></div><div></div></div></div>		
General Product Approval	EMV	For use in hazardous locations
<div><div><div> EG-Konf.</div><div></div><div> RCM</div><div>CCC-Ex</div><div> IECEx</div><div> ATEX</div></div></div>		
last modified:		
3/10/2026 		