

product type designation



OLM/P11 V4.1

spare part SIPLUS NET OLM/P11 V4.0 based on 6GK1503-2CA01 with conformal coating, -25...+60 °C, optical link module with 1 RS-485 and 1 plastic FOC interface (2 BFOC sockets), with signaling contact and test port

product brand name

SIPLUS

Technical Product Detail Page

<https://www.modulplc.com/?s=6AG1503-2CA01-2AA0>

ambient conditions

ambient temperature

- in horizontal mounting position / during operation
- during storage and transport

60 ... -25 °C
70 ... -40 °C

installation altitude / at height above sea level / maximum

5000 m

ambient condition / relating to ambient temperature - air pressure - installation altitude

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

relative humidity

- with condensation / according to IEC 60068-2-38 / maximum

100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation

chemical resistance / to commercially available cooling lubricants

Yes; incl. airborne diesel and oil droplets

resistance to biologically active substances

- conformity according to EN 60721-3-3

Yes; Class 3B2 mold and fungal spores (excluding fauna); class 3B3 on request

- conformity according to EN 60721-3-6

Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)

resistance to chemically active substances

- conformity according to EN 60721-3-3

Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *

- conformity according to EN 60721-3-6

Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (Severity degree 3); *

resistance to mechanically active substances

- conformity according to EN 60721-3-3
- conformity according to EN 60721-3-6

Yes; Class 3S4 incl. sand, dust; *
Yes; Class 6S3 incl. sand, dust; *

environmental category / according to IEC 60721 / note

* The supplied plug covers must remain in place on the unused interfaces during operation!

coating / for equipped printed circuit board / according to EN 61086

Yes; Class 2 for high availability

type of coating

- protection against pollution according to EN 60664-3

Yes; protection of the type 1

type of test / of the coating / according to MIL-I-46058C

Yes; coating discoloration during service life possible

product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; conformal coating, class A

standards, specifications, approvals

certificate of suitability

- CE marking

Yes

further information / internet links

<p>internet link</p> <ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	<div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div> <div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div> <div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div> <div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div> <div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div> <div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div> <div> https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 </div>
<p>security information</p> <p>security information</p>	
<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.modulplc.com/?s=6AG1503-2CA01-2AA0 , (V4.7)</p>	
<p>Approvals / Certificates</p>	
<p>General Product Approval</p>	
<div> Manufacturer Declaration   China RoHS  China RoHS </div>	
<p>General Product Approval EMV</p>	
<div>    </div>	

last modified:
3/10/2026