



Figure similar

SIPLUS S7-1500 AI 8xU/I/RTD/TC based on 6ES7531-7KF00-0AB0 with conformal coating, -40...+70 °C, analog input module 16-bit resolution, accuracy 0.3%, 8 channels in groups of 8, 4 channels for RTD measurement, common mode voltage 10 V; diagnostics; hardware interrupts including infeed element, shielding bracket and shield terminal

General information	
Product type designation	AI 8xU/I/RTD/TC ST
Firmware version	
• FW update possible	Yes
based on	6ES7531-7KF00-0AB0
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Prioritized startup	No
• Measuring range scalable	No
• Scalable measured values	No
• Adjustment of measuring range	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Operating mode	
• Oversampling	No
• MSI	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	255 mA; with 19.2 V supply
Encoder supply	
24 V encoder supply	
• Short-circuit protection	Yes
• Output current, max.	20 mA; Max. 47 mA per channel for a duration < 10 s
Power	
Power consumption from the backplane bus	0.7 W
Power loss	
Power loss, typ.	2.7 W
Analog inputs	
Number of analog inputs	8; > +60 °C max. 2x ±20 mA or 4x ±10 V or 4x RTD permissible
• For current measurement	8

<ul style="list-style-type: none"> • For voltage measurement 	8
<ul style="list-style-type: none"> • For resistance/resistance thermometer measurement 	4
<ul style="list-style-type: none"> • For thermocouple measurement 	8
permissible input voltage for voltage input (destruction limit), max.	28.8 V
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	150 Ohm, 300 Ohm, 600 Ohm, Pt100, Pt200, Ni100: 1.25 mA; 6 000 Ohm, Pt500, Pt1000, Ni1000, LG-Ni1000: 0.625 mA; PTC: 0.472 mA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • 0 to +5 V 	No
<ul style="list-style-type: none"> • 0 to +10 V 	No
<ul style="list-style-type: none"> • 1 V to 5 V 	Yes
— Input resistance (1 V to 5 V)	100 kΩ
<ul style="list-style-type: none"> • -1 V to +1 V 	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
<ul style="list-style-type: none"> • -10 V to +10 V 	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
<ul style="list-style-type: none"> • -2.5 V to +2.5 V 	Yes
— Input resistance (-2.5 V to +2.5 V)	10 MΩ
<ul style="list-style-type: none"> • -25 mV to +25 mV 	No
<ul style="list-style-type: none"> • -250 mV to +250 mV 	Yes
— Input resistance (-250 mV to +250 mV)	10 MΩ
<ul style="list-style-type: none"> • -5 V to +5 V 	Yes
— Input resistance (-5 V to +5 V)	100 kΩ
<ul style="list-style-type: none"> • -50 mV to +50 mV 	Yes
— Input resistance (-50 mV to +50 mV)	10 MΩ
<ul style="list-style-type: none"> • -500 mV to +500 mV 	Yes
— Input resistance (-500 mV to +500 mV)	10 MΩ
<ul style="list-style-type: none"> • -80 mV to +80 mV 	Yes
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA 	Yes
— Input resistance (0 to 20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
<ul style="list-style-type: none"> • -20 mA to +20 mA 	Yes
— Input resistance (-20 mA to +20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
<ul style="list-style-type: none"> • 4 mA to 20 mA 	Yes
— Input resistance (4 mA to 20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> • type B 	Yes
— Input resistance (Type B)	10 MΩ
<ul style="list-style-type: none"> • type C 	No
<ul style="list-style-type: none"> • Type E 	Yes
— Input resistance (Type E)	10 MΩ
<ul style="list-style-type: none"> • Type J 	Yes
— Input resistance (type J)	10 MΩ
<ul style="list-style-type: none"> • Type K 	Yes
— Input resistance (Type K)	10 MΩ
<ul style="list-style-type: none"> • Type L 	No
<ul style="list-style-type: none"> • Type N 	Yes
— Input resistance (Type N)	10 MΩ
<ul style="list-style-type: none"> • Type R 	Yes
— Input resistance (Type R)	10 MΩ
<ul style="list-style-type: none"> • Type S 	Yes
— Input resistance (Type S)	10 MΩ
<ul style="list-style-type: none"> • Type T 	Yes
— Input resistance (Type T)	10 MΩ
<ul style="list-style-type: none"> • Type TXK/TXK(L) to GOST 	No
Input ranges (rated values), resistance thermometer	

• Cu 10	No
• Cu 10 according to GOST	No
• Cu 50	No
• Cu 50 according to GOST	No
• Cu 100	No
• Cu 100 according to GOST	No
• Ni 10	No
• Ni 10 according to GOST	No
• Ni 100	Yes; Standard/climate
— Input resistance (Ni 100)	10 MΩ
• Ni 100 according to GOST	No
• Ni 1000	Yes; Standard/climate
— Input resistance (Ni 1000)	10 MΩ
• Ni 1000 according to GOST	No
• LG-Ni 1000	Yes; Standard/climate
— Input resistance (LG-Ni 1000)	10 MΩ
• Ni 120	No
• Ni 120 according to GOST	No
• Ni 200 according to GOST	No
• Ni 500	No
• Ni 500 according to GOST	No
• Pt 10	No
• Pt 10 according to GOST	No
• Pt 50	No
• Pt 50 according to GOST	No
• Pt 100	Yes; Standard/climate
— Input resistance (Pt 100)	10 MΩ
• Pt 100 according to GOST	No
• Pt 1000	Yes; Standard/climate
— Input resistance (Pt 1000)	10 MΩ
• Pt 1000 according to GOST	No
• Pt 200	Yes; Standard/climate
— Input resistance (Pt 200)	10 MΩ
• Pt 200 according to GOST	No
• Pt 500	Yes; Standard/climate
— Input resistance (Pt 500)	10 MΩ
• Pt 500 according to GOST	No
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	No
• 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	10 MΩ
• PTC	Yes
— Input resistance (PTC)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— Parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation via RTD	Yes
— Compensation for 0 °C reference point temperature	Yes; fixed value can be set
— Reference channel of the module	Yes
Cable length	
• shielded, max.	800 m; for U/I, 200 m for R/RTD, 50 m for TC
Analog value generation for the inputs	

Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	2,5 / 16,67 / 20 / 100 ms
• Basic conversion time, including integration time (ms)	9 / 23 / 27 / 107 ms
— additional conversion time for wire-break monitoring	9 ms (to be considered in R/RTD/TC measurement)
— additional conversion time for resistance measurement	150 ohm, 300 ohm, 600 ohm, Pt100, Pt200, Ni100: 2 ms, 6000 ohm, Pt500, Pt1000, Ni1000, LG-Ni1000, PTC: 4 ms
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10 Hz
• Time for offset calibration (per module)	Basic conversion time of the slowest channel
Smoothing of measured values	
• Parameterizable	Yes
• Step: None	Yes
• Step: low	Yes
• Step: Medium	Yes
• Step: High	Yes
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes
• for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	820 Ω
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with two-wire connection	Yes; Only for PTC
• for resistance measurement with three-wire connection	Yes; All measuring ranges except PTC; internal compensation of the cable resistances
• for resistance measurement with four-wire connection	Yes; All measuring ranges except PTC
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.02 %
Temperature error (relative to input range), (+/-)	0.005 %/K; With TC type T 0.02 $\pm$ % / K
Crosstalk between the inputs, max.	-80 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.02 %
Temperature error of internal compensation	± 6 °C
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.4 %
• Current, relative to input range, (+/-)	0.4 %
• Resistance, relative to input range, (+/-)	0.4 %
• Resistance thermometer, relative to input range, (+/-)	Ptxxx standard: ± 1.5 K, Ptxxx climate: ± 0.5 K, Nixxx standard: ± 0.5 K, Nixxx climate: ± 0.3 K
• Thermocouple, relative to input range, (+/-)	Type B: > 600 °C ± 4.6 K, type E: > -200 °C ± 1.5 K, type J: > -210 °C ± 1.9 K, type K: > -200 °C ± 2.4 K, type N: > -200 °C ± 2.9 K, type R: > 0 °C ± 4.7 K, type S: > 0 °C ± 4.6 K, type T: > -200 °C ± 2.4 K
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.1 %
• Resistance, relative to input range, (+/-)	0.1 %
• Resistance thermometer, relative to input range, (+/-)	Ptxxx standard: ± 0.7 K, Ptxxx climate: ± 0.2 K, Nixxx standard: ± 0.3 K, Nixxx climate: ± 0.15 K
• Thermocouple, relative to input range, (+/-)	Type B: > 600 °C ± 1.7 K, type E: > -200 °C ± 0.7 K, type J: > -210 °C ± 0.8 K, type K: > -200 °C ± 1.2 K, type N: > -200 °C ± 1.2 K, type R: > 0 °C ± 1.9 K, type S: > 0 °C ± 1.9 K, type T: > -200 °C ± 0.8 K
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	40 dB
• Common mode voltage, max.	10 V
• Common mode interference, min.	60 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case

Diagnoses	
• Monitoring the supply voltage	Yes
• Wire break	Yes; Only for 1 to 5 V, 4 to 20 mA, TC, R, and RTD
• Overflow/Underflow	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
Permissible potential difference	
between the inputs (UCM)	20 V DC
Between the inputs and MANA (UCM)	10 V DC
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262
Suitable for applications according to CQI-9	Yes; Based on AMS 2750 E
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	38.6 kg
— global warming potential, (during production) [CO2 eq]	14.4 kg
— global warming potential, (during operation) [CO2 eq]	24.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.44 kg
Security	
signed firmware update	No
data integrity	No
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost)
• horizontal installation, max.	70 °C; = Tmax
• vertical installation, min.	-40 °C; = Tmin
• vertical installation, max.	40 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity

60721-3-3	degree 3); *																																													
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *																																													
Use on ships/at sea																																														
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request																																													
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *																																													
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *																																													
Usage in industrial process technology																																														
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)																																													
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)																																													
Remark																																														
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!																																													
Conformal coating																																														
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability																																													
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection																																													
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life																																													
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A																																													
Dimensions																																														
Width	35 mm																																													
Height	147 mm																																													
Depth	129 mm																																													
Weights																																														
Weight, approx.	310 g																																													
Other																																														
Note:	Additional basic error and noise for integration time = 2.5 ms: Voltage: ±250 mV (±0.02%), ±80 mV (±0.05%), ±50 mV (±0.05%); resistance: 150 ohms ±0.02%; resistance thermometer: Pt100 climate: ±0.08 K, Ni100 climate: ±0.08 K; thermocouple: Type B, R, S: ±3 K, type E, J, K, N, T: ±1 K																																													
Classifications																																														
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>16</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-01</td></tr><tr><td>ETIM</td><td>10</td><td>EC001420</td></tr><tr><td>ETIM</td><td>9</td><td>EC001420</td></tr><tr><td>ETIM</td><td>8</td><td>EC001420</td></tr><tr><td>ETIM</td><td>7</td><td>EC001420</td></tr><tr><td>IDEA</td><td>4</td><td>3562</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	16	27-24-22-01	eClass	14	27-24-22-01	eClass	12	27-24-22-01	eClass	9.1	27-24-22-01	eClass	9	27-24-22-01	eClass	8	27-24-22-01	eClass	7.1	27-24-22-01	eClass	6	27-24-22-01	ETIM	10	EC001420	ETIM	9	EC001420	ETIM	8	EC001420	ETIM	7	EC001420	IDEA	4	3562	UNSPSC	15	32-15-17-05
	Version	Classification																																												
eClass	16	27-24-22-01																																												
eClass	14	27-24-22-01																																												
eClass	12	27-24-22-01																																												
eClass	9.1	27-24-22-01																																												
eClass	9	27-24-22-01																																												
eClass	8	27-24-22-01																																												
eClass	7.1	27-24-22-01																																												
eClass	6	27-24-22-01																																												
ETIM	10	EC001420																																												
ETIM	9	EC001420																																												
ETIM	8	EC001420																																												
ETIM	7	EC001420																																												
IDEA	4	3562																																												
UNSPSC	15	32-15-17-05																																												
Approvals / Certificates																																														
General Product Approval																																														



[China RoHS](#)

[Manufacturer Declaration](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)



For use in hazardous locations

Maritime application

Environment



last modified:

10/23/2025