



Figure similar

SIPLUS S7-1500 CM PTP RS232 HF based on 6ES7541-1AD00-0AB0 with conformal coating, -40...+70 °C, start up -25 °C, communications module for serial connection RS-232, Freeport, 3964 (R), USS, MODBUS RTU master, slave, 115200 Kbit/s, 9-pin D-sub plug

General information	
Product type designation	CM PtP RS 232 HF
based on	6ES7541-1AD00-0AB0
Product function	
• I&M data	Yes; I&M 0
• Fast startup	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Input current	
Current consumption (rated value)	35 mA; From the backplane bus
Power	
Power consumption from the backplane bus	0.65 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Inputs	8 byte
Interface types	
RS 232	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	15 m
• RS 232 auxiliary signals	RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	4 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	4 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
Modbus RTU master	
— Address area	1 to 247, extended 1 to 65535

— max. number of devices	1
Modbus RTU device	
— Address area	1 to 247, extended 1 to 65535
Telegram buffer	
• Buffer memory for telegrams	8 kbyte
• Number of telegrams which can be buffered	255
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	No
Diagnoses	
• Wire break	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Receive RxD	Yes; Yellow LED
• Transmit TxD	Yes; Yellow LED
Potential separation	
between backplane bus and interface	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
• horizontal installation, max.	70 °C
• vertical installation, min.	-40 °C; = Tmin; Startup @ -25 °C
• vertical installation, max.	40 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level

LC3 (salt spray) and level LB3 (oil)																																														
Remark																																														
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!																																													
Conformal coating																																														
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability																																													
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection																																													
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life																																													
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A																																													
Decentralized operation																																														
to SIMATIC S7-300	Yes																																													
to SIMATIC S7-400	Yes																																													
to SIMATIC S7-1500	Yes																																													
to standard PROFINET controller	Yes																																													
Dimensions																																														
Width	35 mm																																													
Height	147 mm																																													
Depth	127 mm																																													
Weights																																														
Weight, approx.	0.22 kg																																													
Classifications																																														
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>16</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-08</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-08</td></tr><tr><td>ETIM</td><td>10</td><td>EC001423</td></tr><tr><td>ETIM</td><td>9</td><td>EC001423</td></tr><tr><td>ETIM</td><td>8</td><td>EC001423</td></tr><tr><td>ETIM</td><td>7</td><td>EC001423</td></tr><tr><td>IDEA</td><td>4</td><td>3564</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	16	27-24-22-08	eClass	14	27-24-22-08	eClass	12	27-24-22-08	eClass	9.1	27-24-22-08	eClass	9	27-24-22-08	eClass	8	27-24-22-08	eClass	7.1	27-24-22-08	eClass	6	27-24-22-08	ETIM	10	EC001423	ETIM	9	EC001423	ETIM	8	EC001423	ETIM	7	EC001423	IDEA	4	3564	UNSPSC	15	32-15-17-05
	Version	Classification																																												
eClass	16	27-24-22-08																																												
eClass	14	27-24-22-08																																												
eClass	12	27-24-22-08																																												
eClass	9.1	27-24-22-08																																												
eClass	9	27-24-22-08																																												
eClass	8	27-24-22-08																																												
eClass	7.1	27-24-22-08																																												
eClass	6	27-24-22-08																																												
ETIM	10	EC001423																																												
ETIM	9	EC001423																																												
ETIM	8	EC001423																																												
ETIM	7	EC001423																																												
IDEA	4	3564																																												
UNSPSC	15	32-15-17-05																																												
Approvals / Certificates																																														
General Product Approval																																														
<div><div> EG-Konf.</div><div>China RoHS</div><div>Manufacturer Declaration</div><div></div><div> UL</div><div></div></div>																																														
General Product Approval	EMV	For use in hazardous locations																																												
	 EG-Konf.		 RCM	 CCC	 ATEX																																									
For use in hazardous locations	Maritime application																																													



IECEX



DNV

last modified:

10/23/2025 