

SIMATIC IPC627E (Box PC), UHD Graphics onboard; DP/DVI-D; 3x Gigbit Ethernet (IE/PN); 6x USB V3.1 Gen.2; 1x serial (COM 1); RAID controller onboard; Watchdog, temperature and fan monitoring; Core i7-8700 (6C/12T, 3.2(4.6) GHz, 12 MB cache, VT-d, AMT); M.2 SSD NVMe 512 GB; HDD 2.5" SATA 320 GB internal; 16 GB DDR4-2666 (2x8); 110/230 V AC industrial power supply unit with NAMUR; power supply cable Europe; Windows 10 Enterprise 2016 LTSC, 64 bit, MUI (en, de, fr, it, es) For Core i7; without expansion (software); without expansion (HW); 2x PCI

General information	
Product type designation	IPC627E
Installation type/mounting	
Mounting	Wall mounting, portrait mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	100/240 V AC (autorange); 24 V DC
Line frequency	
• Rated value 50 Hz	Yes
• Rated value 60 Hz	Yes
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Celeron G4900 (2C/2T, 3.1 GHz, 2 MB cache; VT-d); Core i3-8100 (4C/4T, 3.6 GHz, 6 MB cache, VT-d); Core i7-8700 (6C/12T, 3.2 (4.6) GHz, 12 MB cache, VT-d, AMT)
Chipset	Intel C246
Graphic	
Graphics controller	Intel UHD Graphics 630 (Core i); Intel UHD Graphics 610 (Celeron)
Drives	
Hard disk	2.5" SATA ≥ 320 GB
SSD	Yes; SSD M.2 NVMe 512 GB; SSD 2.5" SATA 480 / 960 GB; RAID1 2x SSD 2.5" SATA 480 / 960 GB in removable drive bay
Storage	
Type of memory	DDR4-2666 DIMM
Main memory	4 / 8 / 16 / 32 / 64 GB
Capacity of main memory, max.	64 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time
Hardware configuration	
Slots	
• Number of PCI slots	3; Optional
• Number of PCI slots	5; Optional
Interfaces	
Number of industrial Ethernet interfaces	3; 3x Ethernet (RJ45)
serial interface	1x COM
Video interfaces	
• Graphics interface	2x DisplayPort; 1x DVI-D
Industrial Ethernet	
• Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	1x power, 3x user
Integrated Functions	

Monitoring functions			
<ul style="list-style-type: none">• Temperature monitoring	Yes		
<ul style="list-style-type: none">• Fan	Yes		
<ul style="list-style-type: none">• Monitoring function via network	Optional		
Degree and class of protection			
IP degree of protection	IP20		
Standards, approvals, certificates			
CE mark	Yes		
UL approval	Yes		
cULus	Yes; UL 61010-2-201 Second Edition; CAN/CSA-C22.2 No. 61010-2-201 Second Edition		
RCM (formerly C-TICK)	Yes		
KC approval	Yes		
EAC (formerly Gost-R)	Yes		
FCC	Yes		
BSMI	Yes		
Use in hazardous areas			
<ul style="list-style-type: none">• cULus Class I Zone 2, Division 2	Yes; Optional		
Marine approval			
<ul style="list-style-type: none">• American Bureau of Shipping (ABS)	Yes; Only with SSD		
<ul style="list-style-type: none">• Bureau Veritas (BV)	Yes; Only with SSD		
<ul style="list-style-type: none">• Det Norske Veritas (DNV)	Yes; Only with SSD		
<ul style="list-style-type: none">• Korean Register of Shipping (KRS)	Yes; Only with SSD		
<ul style="list-style-type: none">• Lloyds Register of Shipping (LRS)	Yes; Only with SSD		
<ul style="list-style-type: none">• Nippon Kaiji Kyokai (Class NK)	Yes; Only with SSD		
<ul style="list-style-type: none">• Chinese Classification Society (CCS)	Yes; Only with SSD		
Ambient conditions			
Ambient temperature during operation			
<ul style="list-style-type: none">• min.	5 °C		
<ul style="list-style-type: none">• max.	55 °C		
Ambient temperature during storage/transportation			
<ul style="list-style-type: none">• min.	-20 °C		
<ul style="list-style-type: none">• max.	60 °C		
Vibrations			
<ul style="list-style-type: none">• Vibration resistance during operation acc. to IEC 60068-2-6	tested according to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm; 58 Hz to 500 Hz 9.8 m/s² (1 g)		
Operating systems			
pre-installed operating system	Windows 10 Enterprise 2016 LTSP or 2019 LTSC or 2021 LTSC 64 bit, MUI		
without operating system	Yes; Optional		
pre-installed operating system			
<ul style="list-style-type: none">• Windows 10 Enterprise	Yes; Windows 10 Enterprise 2016 LTSP or 2019 LTSC or 2021 LTSC 64 bit, MUI		
Dimensions			
Width	314 mm		
Height	93 mm; For variant 5x PCI(e): 155 mm		
Depth	301 mm; incl. mounting rail		
Classifications			
		Version	Classification
	eClass	16	19-20-01-02
	eClass	14	19-20-01-02
	eClass	12	19-20-01-02
	eClass	9.1	19-20-01-02
	eClass	9	19-20-01-02
	eClass	8	19-20-01-02
	eClass	7.1	19-20-01-02
	eClass	6	19-20-01-02
	ETIM	10	EC001413
	ETIM	9	EC001413

ETIM	8	EC001413
ETIM	7	EC001413

Approvals / Certificates

General Product Approval



EG-Konf.



[Manufacturer Declaration](#)



UL



[inspection certificate](#)

General Product Approval

Maritime application



RCM



[BIS CRS](#)



EG-Konf.



ABS

Maritime application



BUREAU
VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

other

Dangerous goods

Environment



CB

[Dangerous goods information](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

last modified:

6/10/2026