

protective cover for MP 277 10" Touch up to product version "ES 14", thin client 10" up to "ES 03" (6AV6646-0AA21-2AX0) with narrow frame, scope of supply: 2 cover frames, 2 base frames, 2 protective covers



| General information                               |                                                                                                                          |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Product type designation                          | Protective cover MP277 10" touch                                                                                         |
| Installation type/mounting                        |                                                                                                                          |
| Mounting in portrait format possible              | Yes                                                                                                                      |
| Mounting in landscape format possible             | Yes                                                                                                                      |
| Degree and class of protection                    |                                                                                                                          |
| IP (at the front)                                 | IP65                                                                                                                     |
| Standards, approvals, certificates                |                                                                                                                          |
| CE mark                                           | Yes                                                                                                                      |
| Ambient conditions                                |                                                                                                                          |
| Ambient temperature during operation              |                                                                                                                          |
| • min.                                            | -40 °C                                                                                                                   |
| • max.                                            | 80 °C                                                                                                                    |
| Ambient temperature during storage/transportation |                                                                                                                          |
| • min.                                            | -40 °C                                                                                                                   |
| • max.                                            | 80 °C                                                                                                                    |
| Relative humidity                                 |                                                                                                                          |
| • Operation, max.                                 | 95 %                                                                                                                     |
| Mechanics/material                                |                                                                                                                          |
| Material                                          |                                                                                                                          |
| • plastic                                         | Yes                                                                                                                      |
| Dimensions                                        |                                                                                                                          |
| Width                                             | 355.8 mm                                                                                                                 |
| Height                                            | 294 mm                                                                                                                   |
| Thickness                                         | 7.8 mm                                                                                                                   |
| Mounting cutout, width                            | 310 mm                                                                                                                   |
| Mounting cutout, height                           | 248 mm                                                                                                                   |
| Weights                                           |                                                                                                                          |
| Weight (without packaging)                        | 750 g                                                                                                                    |
| Scope of supply                                   |                                                                                                                          |
| Delivery quantity in pieces                       |                                                                                                                          |
| • Parts per unit                                  | 2; 2 cover frames, 2 base frames, 2 protective covers                                                                    |
| Other                                             |                                                                                                                          |
| Merchandise                                       | No                                                                                                                       |
| Manufacturer name                                 | SIEMENS AG                                                                                                               |
| Manufacturer's address                            | Gleiwitzerstraße 555, 90475 Nuremberg, Germany                                                                           |
| Target devices                                    | For MP277 10" touch up to product version "ES 14 ", Thin Client 10" up to "ES 03" (6AV6646-0AA21-2AX0) with narrow frame |
| Classifications                                   |                                                                                                                          |

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 16      | 27-33-02-92    |
| eClass | 14      | 27-33-02-92    |
| eClass | 12      | 27-33-02-92    |
| eClass | 9.1     | 27-33-02-92    |
| eClass | 9       | 27-33-02-92    |
| eClass | 8       | 27-24-92-03    |
| eClass | 7.1     | 27-24-92-03    |
| eClass | 6       | 27-24-92-03    |
| ETIM   | 10      | EC002584       |
| ETIM   | 9       | EC002584       |
| ETIM   | 8       | EC002584       |
| ETIM   | 7       | EC002584       |
| IDEA   | 4       | 3552           |
| UNSPSC | 15      | 32-15-17-03    |

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://www.modulplc.com/?s=6AV6671-3CK00-0AX0>

last modified:

5/22/2024 