

SIMATIC IPC377G (basic panel PC); 22" singletouch (1920 x 1080); 2x 10/100/1000 Mbps Ethernet RJ45; 2x DisplayPort graphic; 4x USB 3.1; 2x M.2 extension slot; 24 V DC power supply Atom x6413E (up to 3.0 GHz); 8 GB RAM; 4x USB+2x COM; Windows10 Enterprise 2019 LTSC, 64 bit; MUI (en,de,fr,it,es); 256 GB SSD; ;

General information	
Product type designation	IPC377G
Display	
Design of display	22" TFT touch
Screen diagonal	22 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Touch operation	
• Design as touch screen	Yes; Analog-resistive
Installation type/mounting	
Mounting	Panel mount and VESA, horizontal and vertical
Design	Panel PC, built-in unit
central design	Yes
Mounting in portrait format possible	Yes
Supply voltage	
Type of supply voltage	24 V DC
Mains buffering	
• Mains/voltage failure stored energy time	10 ms
Processor	
Processor type	Intel Atom X6413E
Storage	
Type of memory	DDR4
Main memory	4 GB, 8 GB, 16 GB
Capacity of main memory, max.	16 Gbyte
Interfaces	
Number of industrial Ethernet interfaces	2; 2x RJ45 (independent)
Video interfaces	
• Graphics interface	2x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Protocols	
Protocols (Ethernet)	
• TCP/IP	Yes
Interrupts/diagnostics/status information	
LED status display	POWER, HDD
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Fan	No
Degree and class of protection	
IP (at the front)	IP65

IP (rear)	IP40																																							
Standards, approvals, certificates																																								
CE mark	Yes																																							
CSA approval	Yes																																							
UL approval	Yes																																							
RCM (formerly C-TICK)	Yes																																							
KC approval	Yes																																							
EAC (formerly Gost-R)	Yes																																							
FCC	Yes																																							
BSMI	Yes																																							
Dust protection	Protection against foreign bodies > 1 mm																																							
Ambient conditions																																								
Ambient temperature during operation																																								
<ul style="list-style-type: none">min.max.	0 °C 50 °C; when installed vertically in horizontal format, vertical inclination maximum 45° or when installed upright in vertical format																																							
Ambient temperature during storage/transportation																																								
<ul style="list-style-type: none">min.max.	-20 °C 70 °C																																							
Relative humidity																																								
<ul style="list-style-type: none">Operation, max.	85 %																																							
Vibrations																																								
<ul style="list-style-type: none">Vibration resistance during operation acc. to IEC 60068-2-6	Tested according to IEC 60068-2-6: 5 Hz to 8.4 Hz: 3.5 mm, 8.4 Hz to 500 Hz: 9.8 m/s²																																							
Operating systems																																								
without operating system	Yes																																							
pre-installed operating system																																								
<ul style="list-style-type: none">Windows 10 Enterprise	Yes																																							
Dimensions																																								
Width	652 mm																																							
Height	443 mm																																							
Depth	209 mm																																							
Width of the housing front	539.79999 mm																																							
Height of housing front	334.39999 mm																																							
Mounting cutout, width	522.2 mm																																							
Mounting cutout, height	316.8 mm																																							
mounting depth	99.7 mm																																							
Weights																																								
Weight, approx.	7.1 kg																																							
Classifications																																								
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>16</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>14</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>12</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>9.1</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>9</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>8</td><td>27-24-23-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-23-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-23-01</td></tr><tr><td>ETIM</td><td>10</td><td>EC001414</td></tr><tr><td>ETIM</td><td>9</td><td>EC001414</td></tr><tr><td>ETIM</td><td>8</td><td>EC001414</td></tr><tr><td>ETIM</td><td>7</td><td>EC001414</td></tr></table>		Version	Classification	eClass	16	19-20-01-03	eClass	14	19-20-01-03	eClass	12	19-20-01-03	eClass	9.1	19-20-01-03	eClass	9	19-20-01-03	eClass	8	27-24-23-01	eClass	7.1	27-24-23-01	eClass	6	27-24-23-01	ETIM	10	EC001414	ETIM	9	EC001414	ETIM	8	EC001414	ETIM	7	EC001414
	Version	Classification																																						
eClass	16	19-20-01-03																																						
eClass	14	19-20-01-03																																						
eClass	12	19-20-01-03																																						
eClass	9.1	19-20-01-03																																						
eClass	9	19-20-01-03																																						
eClass	8	27-24-23-01																																						
eClass	7.1	27-24-23-01																																						
eClass	6	27-24-23-01																																						
ETIM	10	EC001414																																						
ETIM	9	EC001414																																						
ETIM	8	EC001414																																						
ETIM	7	EC001414																																						
Approvals / Certificates																																								
General Product Approval																																								



[Miscellaneous](#)



General Product Approval

EMV

Dangerous goods



[BIS CRS](#)



[Test Summary Report
UN 38.3](#)

[Dangerous goods in-
formation](#)

last modified:

6/10/2026