

SIMATIC IPC477E PRO fully protected IP65; 19" multi-touch (1366 x 768); neutral front; for support arm (expandable, round pipe) 4 USB (back); without USB (front); Ethernet (10/100/1000 Core i5-6442EQ; 3x Gbit Ethernet (IE/PN); 16 GB; without RS 232/RS485; without PCIe; Windows 10 Enterprise 2019 LTSC (64-bit), MUI (en,de,fr,it,es), for Celeron, i3 and i5, Without replaceable mass storage; 240 GB solid-state drive SATA Without SIMATIC software 24 V DC industrial power supply

Standards, approvals, certificates		
Ecological footprint		
● environmental product declaration	Yes	
Global warming potential		
— global warming potential, (total) [CO2 eq]	836 kg	
— global warming potential, (during production) [CO2 eq]	143 kg	
— global warming potential, (during operation) [CO2 eq]	720 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-30.2 kg	
Approvals / Certificates		
General Product Approval		
For use in hazardous locations		
<div><div>Miscellaneous</div><div><div>IECEx</div></div></div>		
For use in hazardous locations		
Maritime application		
<div><div>Miscellaneous</div><div><div>IECEx</div><div>ATEX</div><div>ABS</div><div>BUREAU VERITAS</div><div>LRS</div></div></div>		
Maritime application	Dangerous goods	Environment
NK / Nippon Kaiji Kyokai	Dangerous goods information	Test Summary Report UN 38.3
		

last modified:

5/23/2026