SIEMENS

## Data sheet 6AV7251-7RC00-0GA0

SIMATIC IPC477E PRO fully protected IP65; 19" multi-touch (1366 x 768); neutral front; for support arm (expandable, round pipe) 4 USB (back); without USB (front); Ethernet (10/100/1000 Xeon E3-1505L; 3x Gbit Ethernet (IE/PN); 16 GB; without RS 232/RS485; without PCIe; without operating system; Without replaceable mass storage; 480 GB solid-state drive SATA Without SIMATIC software 24 V DC industrial power supply

| Standards, approvals, certificates | |
|---|---|
| Ecological footprint | |
| ● environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 836 kg |
| — global warming potential, (during production) [CO2 eq] | 143 kg |
| — global warming potential, (during operation) [CO2 eq] | 720 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -30.2 kg |

**Approvals / Certificates**

| General Product Approval | | | | | For use in hazard-ous locations |
|---|---|---|---|---|---|
| Miscellaneous | UL | EAC | BIS CRS | China RoHS | IECEx |

| For use in hazardous locations | | | Maritime application | | |
|---|---|---|---|---|---|
| Miscellaneous | IECEx | ATEX | ABS | BUREAU VERITAS | LRS |

| Maritime application | Dangerous goods | | Environment |
|---|---|---|---|
| NK / Nippon Kaiji Ky-okai | Dangerous goods in-formation | Test Summary Report UN 38.3 | EPD |

**last modified:** 5/23/2026


Subject to change without notice
© Copyright Modulplc