SIEMENS

## Data sheet 6AV7252-7CF10-2AB0

SIMATIC IPC PX-39A PRO 19" multi-touch (1920 x 1080); fully enclosed IP65; 4 USB (back); without USB (front); Ethernet (10/100/1000); Intel Xeon W-11865MLE (1.5/4.5 GHz, 8C/16T); 32 GB with ECC; 1st mass storage: M.2 SSD 256 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC with processor W-11865MLE; supporting foot (expandable, flange at bottom) with USB flash drive (restore image; D&D) 24 V DC industrial power supply (premium, power failure, isolated, bridging time)

| | |
|---|---|
| **General information** | |
| Product type designation | PX-39A PRO |
| **Display** | |
| Design of display | TFT widescreen display, LED backlighting |
| Screen diagonal | 19 in |
| Display width | 409 mm |
| Display height | 230 mm |
| Resolution (pixels) | |
| ● Horizontal image resolution | 1 920 pixel |
| ● Vertical image resolution | 1 080 pixel |
| **Control elements** | |
| Touch operation | |
| ● Design as touch screen | Yes; Projective-capacitive |
| ● Design as multi-touch screen | Yes; Projective-capacitive |
| **Installation type/mounting** | |
| Mounting | For mounting on stand or supporting bracket |
| Design | Panel PC on pedestal or supporting arm |
| Support arm mounting | Yes; Suitable for support arm and extension components (please refer to manual) |
| Stand mounting | Yes; prepared for base and extension components (please refer to manual) |
| Mounting in portrait format possible | No |
| **Supply voltage** | |
| Type of supply voltage | 24 V DC |
| Rated value (DC) | 24 V |
| Mains buffering | |
| ● Mains/voltage failure stored energy time | 20 ms |
| **Processor** | |
| Processor type | Intel Celeron 6600HLE (2.1 GHz, 2C/2T) Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/6T) Intel Xeon W-11555MLE (1.9/4.4 GHz, 6C/12T) Intel Xeon W-11865MLE (1.5/4.5 GHz, 8C/16T) |
| Chipset | Intel® RM590E |
| **Graphic** | |
| Graphics controller | Intel® UHD Graphics 16 EUs (for Intel® Celeron® 6600HLE and Intel® Xeon® W-11155MLE) / Intel® UHD Graphics 32 EUs (for Intel® Xeon® W-11555MLE and Intel® Xeon® W-11865MLE) |
| **Drives** | |
| Hard disk | M.2 SSD ≥ 240 GB |
| SSD | Yes; ≥ 240 GB optional |
| **Storage** | |
| Type of memory | DDR4-2400 SO-DIMM |
| Main memory | 4 / 8 / 16 / 32 GB; ECC optional |
| Capacity of main memory, max. | 32 Gbyte |
| **Data areas and their retentivity** | |
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte; 128 KB can be stored in the buffer time |
| **Hardware configuration** | |
| Slots | |
| ● Number of PCI slots | 0; Different to the built-in unit |


© Copyright Modulplc

| | |
|---|---|
| ● Number of compact flash slots | 0 |
| **Interfaces** | |
| Number of industrial Ethernet interfaces | 4; 4x Gigabit Ethernet (IE/PN) |
| serial interface | 1x (optional) COM (RS 232 / 485 / 422; selectable) |
| Video interfaces | |
| ● Graphics interface | 2x DisplayPort (DP1.4-capable): maximum 4096 × 2304 / 60 Hz / 36 bit |
| Industrial Ethernet | |
| ● Industrial Ethernet interface | |
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| **Interrupts/diagnostics/status information** | |
| LED status display | No |
| Bus diagnostics | Yes |
| **Integrated Functions** | |
| Monitoring functions | |
| ● Temperature monitoring | Yes |
| ● Fan | No |
| ● Monitoring function via network | Optional |
| **Degree and class of protection** | |
| IP (at the front) | IP65 |
| IP (rear) | IP65 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| UKCA mark | Yes |
| CSA approval | Yes |
| UL approval | Yes; UL 61010-2-201 Second Edition, File E85972 |
| ● UL 508 | No |
| cULus | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| FCC | Yes |
| BSMI | No; in preparation |
| BIS | Yes |
| Use in hazardous areas | |
| ● CCC Ex | Yes |
| Marine approval | |
| ● Germanischer Lloyd (GL) | Yes |
| ● American Bureau of Shipping (ABS) | Yes |
| ● Bureau Veritas (BV) | Yes |
| ● Det Norske Veritas (DNV) | Yes |
| ● Korean Register of Shipping (KRS) | Yes |
| ● Lloyds Register of Shipping (LRS) | Yes |
| ● Nippon Kaiji Kyokai (Class NK) | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |
| ● max. | 45 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 2 000 m |
| Relative humidity | |
| ● Operation, max. | 85 % |
| Vibrations | |
| ● Vibration resistance during operation acc. to IEC 60068-2-6 | tested according to IEC 60068-2-6; 5 Hz to 8.4 Hz: 3.5 mm, 8.4 Hz up to 200 Hz: 9.8 m/s² |
| **Operating systems** | |


© Copyright Modulplc

| | |
|---|---|
| pre-installed operating system | Windows 10 IoT Enterprise 2021 LTSC, Windows 11 IoT Enterprise 2024 LTSC, Industrial OS |
| without operating system | Yes; Optional |
| pre-installed operating system | |
| ● Windows 7 | No |
| ● Windows 10 Enterprise | Yes; Windows 10 IoT Enterprise 2021 LTSC |
| ● Windows 11 | Yes; Windows 11 IoT Enterprise 2024 LTSC |
| **Dimensions** | |
| Width of the housing front | 462 mm |
| Height of housing front | 292 mm; Without basic adapter |
| **Weights** | |
| Weight, approx. | 8.2 kg |
| **Approvals / Certificates** | |

**General Product Approval**

EG-Konf. UL RCM BIS CRS

| General Product Approval | For use in hazardous locations |
|---|---|

EG-Konf. IECEx Miscellaneous IECEx

| For use in hazardous locations | Dangerous goods |
|---|---|

ATEX Dangerous goods information

**last modified:** 6/10/2026


© Copyright Modulplc