



label holder for self-inscription, flat, frame rounded off at the bottom for labeling plate 16.05 mm x 26.3 mm, for gluing, for the operator controls of the Extension Units for PRO devices (template for labeling for download is available), not suitable for labeling of EMERGENCY STOP button, scope of supply: 12 label holders, 12 transparent covers

General information			
Product type designation		Label holder	
Standards, approvals, certificates			
CE mark		Yes	
UKCA mark		Yes	
Ambient conditions			
Ambient temperature during operation			
• min.		0 °C	
• max.		50 °C	
Ambient temperature during storage/transportation			
• min.		-20 °C	
• max.		60 °C	
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.		3 500 m	
Relative humidity			
• Operation, max.		90 %	
• Condensation permissible		No	
Mechanics/material			
Material			
• plastic		Yes	
Dimensions			
Width		29.9 mm	
Height		50 mm	
Depth		3.6 mm	
Mounting diameter		22.3 mm	
Weights			
Weight (without packaging)		33 g	
Scope of supply			
Delivery quantity in pieces		1	
• Parts per unit		12	
Components included		12 label holders, 12 transparent covers, installation instructions	
Other			
printable with laser printer		Yes; Word template available for labeling in SIOS, writable surface area: 28 mm x 16 mm (width x height)	
Target devices		Suitable for Extension Units of the 16:9 HMI/IPC PRO devices (refer to manual)	
Classifications			
		Version	Classification
	eClass	14	27-33-02-92

eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

[China RoHS](#)

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: **40466415**
<https://www.modulplc.com/?s=6AV7674-1LB20-0AA0>

last modified: 6/3/2025 