

SIMATIC IPC MD-34A Desk Dock accessories; MD-34A all configurations; 1x LAN 10/100 Mbps, 2x USB 2.0; 1x RS-232; 1x VGA, DC-in 19 V side; 2x USB 2.0; use the MD-34A power supply cord for the Desk Dock



General information			
Design of the programming device		Mobile computer	
Supply voltage			
Rated value (DC)		19 V	
permissible range, lower limit (AC)		100 V	
permissible range, upper limit (AC)		240 V	
Interfaces			
Number of RS 232 interfaces		1	
Number of USB interfaces		4	
• Type A		4; 2* USB 2.0 in rear I/O 2* USB 2.0 in the side I/O	
Video interfaces			
• analog video signal (VGA)		Yes	
Industrial Ethernet			
• Industrial Ethernet interface		Yes; 1* 10/100 MBits/s	
— 100 Mbps			
• Wake on LAN			
• IAMT (Intel Active Management Technology)		No	
Standards, approvals, certificates			
CE mark		Yes	
Ambient conditions			
Ambient temperature during operation			
• min.		0 °C	
• max.		45 °C	
Ambient temperature during storage/transportation			
• min.		-20 °C	
• max.		60 °C	
Relative humidity			
• Operation, min.		50 %	
• Operation, max.		95 %	
Dimensions			
Width		292 mm	
Height		133 mm	
Depth		99 mm	
Weights			
Weight, approx.		770 mg	
Classifications			
		Version	Classification
	eClass	16	27-33-02-92

eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)


EG-Konf.




RCM

[China RoHS](#)

last modified:

6/13/2026 