

SIMATIC IFP2200 V2 Extended, 22" multi-touch display (16:9) with 1920x1080 pixel resolution, built-in unit, for 24 V DC, DisplayPort, can be placed up to 100 m away HDBaseT, USB on the rear side, neutral design



Figure similar

General information	
Product type designation	IFP2200 V2
Short designation	SIMATIC IFP2200 V2
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in; 22"
Screen diagonal [cm]	56 cm
Display width	476 mm
Display height	268 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	170° x 170°
Resolution (pixels)	
• Image resolution	1 920 x 1 080
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
• Pixel size, horizontal	0.2475 mm
• Pixel size, vertical	0.2475 mm
General features	
• Brightness/contrast	250 cd/m² / 1 000:1
• Detachable from computer unit	100 m; HDBaseT protocol
• Luminance	250 cd/m²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	multi-touch screen
Input device	
• Integrated mouse cursor control	Yes; Also externally via USB
Touch operation	
• Design as touch screen	Yes; Projective-capacitive
• Design as multi-touch screen	Yes; Projective-capacitive
• Monitor keyboard	Yes; If supported by operating system
Installation type/mounting	
Design	Built-in unit
Front mounting	Yes
VESA mounting	Yes; VESA 100 x 100 integrated

Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1 A
Current consumption, max.	1.3 A
Inrush current, max.	2 A
Starting current inrush I ² t	0.5 A ² ·s
Power loss	
Power loss, typ.	24 W
Power loss, max.	30 W
Interfaces	
Number of USB interfaces	2; USB 2.0 type A
USB on the rear	Yes; 2x onboard
Video interfaces	
• DVI-D	No
• DisplayPort	Yes; Display port V1.2
Touch interfaces	
• USB	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4 at the front	Yes
• Enclosure Type 4x at the front	Yes
• Enclosure Type 12 at the front	Yes
Standards, approvals, certificates	
Certificate of suitability	hazardous zone 2/22; shipbuilding
CE mark	Yes
UL approval	Yes; cULus, cUL
cULus	Yes
FM approval	Yes; Class I Div. 2
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	Yes
EMC	CE, EN 55011, EN 61000-6-4, EN 61000-6-2
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO ₂ eq]	424.98835 kg
— global warming potential, (during production) [CO ₂ eq]	90.85845 kg
— global warming potential, (during operation) [CO ₂ eq]	347.89539 kg
— global warming potential, (after end of life cycle) [CO ₂ eq]	-16.20242 kg
Use in hazardous areas	
• ATEX Zone 2	Yes
• ATEX Zone 22	Yes
• IECEx Zone 2	Yes
• IECEx Zone 22	Yes
• FM Class I Division 2	Yes
Marine approval	

<ul style="list-style-type: none">• Germanischer Lloyd (GL)• American Bureau of Shipping (ABS)• Bureau Veritas (BV)• Det Norske Veritas (DNV)• Lloyds Register of Shipping (LRS)• Nippon Kaiji Kyokai (Class NK)	Yes		
	Yes		
	Yes		
	Yes		
	Yes		
	Yes		
Ambient conditions			
Ambient temperature during operation			
<ul style="list-style-type: none">• min.	0 °C		
<ul style="list-style-type: none">• max.	45 °C		
Ambient temperature during storage/transportation			
<ul style="list-style-type: none">• min.	-20 °C		
<ul style="list-style-type: none">• max.	60 °C		
Altitude during operation relating to sea level			
<ul style="list-style-type: none">• Installation altitude above sea level, max.	3 500 m		
Relative humidity			
<ul style="list-style-type: none">• Operation, max.	90 %; no condensation		
Vibrations			
<ul style="list-style-type: none">• Vibration load in operation	10 m/s²		
<ul style="list-style-type: none">• Vibration load during transport/storage	10 m/s²		
Shock testing			
<ul style="list-style-type: none">• Shock load during operation	150 m/s²		
<ul style="list-style-type: none">• shock acceleration during storage/transport	250 m/s²		
Mechanics/material			
Enclosure material (front)	With neutral design		
<ul style="list-style-type: none">• Aluminum	Yes		
<ul style="list-style-type: none">• Aluminum casting	Yes		
<ul style="list-style-type: none">• Glass	Yes; at front		
Enclosure material (rear)	aluminum		
Dimensions			
Width of the housing front	529 mm		
Height of housing front	331 mm		
Mounting cutout, width	513 mm; Tolerance: +1 mm		
Mounting cutout, height	315 mm; Tolerance: +1 mm		
mounting depth	63.4 mm		
Weights			
Weight (without packaging)	6.4 kg		
Weight (with packaging)	8.4 kg		
Classifications			
		Version	Classification
	eClass	16	19-20-02-01
	eClass	14	19-20-02-01
	eClass	12	19-20-02-01
	eClass	9.1	19-20-02-01
	eClass	9	19-20-02-01
	eClass	8	19-20-02-01
	eClass	7.1	19-20-02-01
	eClass	6	19-20-02-01
	ETIM	10	EC004862
	ETIM	9	EC001428
	ETIM	8	EC001428
	ETIM	7	EC001428
	IDEA	4	6675
	UNSPSC	15	43-21-19-02
Approvals / Certificates			
General Product Approval			

[Miscellaneous](#)



[Manufacturer Declaration](#)



General Product Approval

EMV

For use in hazardous locations

[BIS CRS](#)

[China RoHS](#)



For use in hazardous locations



[FM](#)



[Miscellaneous](#)



For use in hazardous locations

Maritime application

[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application

Environment

[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)



last modified:

4/1/2025