SIEMENS

Data sheet 6AV7886-0BA11-1AA0

SIMATIC IPC277G (nanopanel PC); 10" multi-touch (1280 x 800); 3x 10/100/1000 Mbps Ethernet RJ45; 2x display port graphic; 4x USB 3.1, 2x M.2 extension slot; 24 V DC industrial power supply Atom X6413E (2-core); 4 GB RAM / with USB flash drive (documentation); without COM; without mass storage; without hardware extension; without software; ;

General information	
Product type designation	IPC277G
Display	
Design of display	10" TFT multi-touch
Screen diagonal	10 in
Resolution (pixels)	
● Horizontal image resolution	1 280 pixel
● Vertical image resolution	800 pixel
Backlighting	
● MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Touch operation	
● Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
Mounting	For horizontal and vertical mounting
Design	Panel PC, built-in unit
central design	Yes
Mounting in portrait format possible	Yes
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Intel Atom X6211E / X6413E / X6414RE
Chipset	SoC
Graphic	
Graphics controller	Integrated
Drives	
SSD	Yes; 256 Eco / 240 / 480 GB
Storage	
Type of memory	DDR4 SO-DIMM
Main memory	4 / 8 / 16 GB; inband ECC optional
Capacity of main memory, max.	16 Gbyte
Interfaces	
Number of industrial Ethernet interfaces	3; 3x Ethernet (RJ45)
serial interface	without / 1x / 2x COM (RS 232 / 485 / 422; selectable)
Video interfaces	
● Graphics interface	2x DisplayPort
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Protocols	
Protocols (Ethernet)	
● DHCP	Yes
Interrupts/diagnostics/status information	

© Copyright Modulplc

LED status display	No
Integrated Functions	
Monitoring functions	
● Temperature monitoring	Yes
● Fan	No
● Monitoring function via network	Optional
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	20
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	50 °C; from 19", 22", 24": max. 45 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	85 %
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	tested according to IEC 60068-2-6: 5 Hz to 8.4 Hz: 3.5 mm, 8.4 Hz to 200 Hz : 9.8m/s² (1 g) (except DIN Rail) 10 Hz to 58 Hz: 0.0375 mm, 58 Hz to 500 Hz: 4.9 m/s² (0.5 g) (DIN Rail)
Operating systems	
pre-installed operating system	Windows 10 IoT Enterprise 2019 LTSC, 64 bit, MUI
without operating system	Yes; Optional
pre-installed operating system	
● Windows 10 Enterprise	Yes; Windows 10 IoT Enterprise 2019 LTSC, 64 bit, MUI
Dimensions	
Width of the housing front	280 mm
Height of housing front	205 mm
Mounting cutout, width	264 mm
Mounting cutout, height	189 mm
mounting depth	95 mm
Weights	
Weight, approx.	3.2 kg
Approvals / Certificates	

General Product Approval

CCC EAC EG-Konf. Manufacturer Declaration | Declaration of Conformity | Type Examination Certificate

General Product Approval				For use in hazardous locations	
TUEV	China RoHS	EG-Konf.	UKCA	IECEx	ATEX

For use in hazardous locations	Radio Equipment Type Approval Certificate

© Copyright Modulplc

CCC-Ex	Miscellaneous	SUBTEL		Miscellaneous	Miscellaneous

Maritime application

ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Ky-okai	RINA

Railway	Environment
Confirmation	EPD

last modified: 6/11/2026

Subject to change without notice
© Copyright Modulplc