



Figure similar

*** Spare part *** SIMATIC DP, Electronics module f. ET200S, 4 F-DI/3 F-DO 24 V DC/2A PROFIsafe, 30 mm overall width up to Category 3 (EN 954-1)/ SIL2 (IEC61508)/PLD (ISO13849), can also be used in PROFINET configuration with IM 151-3 HF

Supply voltage	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	3.5 W
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	DC
Input current	
• for signal "1", typ.	3.5 mA
Standards, approvals, certificates	
Highest safety class achievable in safety mode	
• acc. to EN 954	3
• Performance level according to ISO 13849-1	d
• SIL acc. to IEC 61508	2
Dimensions	
Width	30 mm
Height	81 mm
Depth	52 mm
Classifications	

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)


EG-Konf.




UL


RCM

General Product Approval

EMV

For use in hazardous locations



[China RoHS](#)


RCM


ATEX

[EM](#)


ATEX

For use in hazardous locations

Functional Safety


UL


ATEX


IECEX

[Miscellaneous](#)

[CCC-Ex](#)

[TUEV](#)

Functional Safety

Maritime application

[Type Examination Certificate](#)


ABS


BUREAU
VERITAS


DNV


LRS

[NK / Nippon Kaiji Kyokai](#)

Maritime application


PRS


RINA

[CCS \(China Classification Society\)](#)

last modified:

7/17/2025 