



SIMATIC DP, ET 200ECO PN, voltage distributor PD 24 V DC; 1x 7/8", 4xM12, Degree of protection IP67

Power loss			
Power loss, typ.	3.5 W		
Potential separation			
between the load voltages	Yes		
Isolation			
tested with			
• 24 V DC circuits	500 V		
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3		
Dimensions			
Width	45 mm		
Height	175 mm		
Depth	49 mm		
Weights			
Weight, approx.	590 g		
Classifications			
		Version	Classification
	eClass	16	27-24-26-92
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03
Approvals / Certificates			
General Product Approval			

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval		EMV	For use in hazardous locations		Maritime application
		China RoHS			CCS (China Classification Society)

last modified:

4/7/2025 