SIEMENS

## Data sheet 6ES7194-3AA00-0BA0

SIMATIC DP, Connection block M12, 7/8" for ET 200ECO, 2x M12 and 2x 7/8", 2 rotary coding switches for PROFIBUS DP, Address setting

| | |
|---|---|
| **Power loss** | |
| Power loss, typ. | 2 W; The power loss depends on the current that you loop through via the connection block. |
| **Dimensions** | |
| Width | 79 mm |
| Height | 60 mm |
| Depth | 29 mm |
| **Weights** | |
| Weight, approx. | 392 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-26-03 |
| eClass | 14 | 27-24-26-03 |
| eClass | 12 | 27-24-26-03 |
| eClass | 9.1 | 27-24-26-03 |
| eClass | 9 | 27-24-26-03 |
| eClass | 8 | 27-24-26-03 |
| eClass | 7.1 | 27-24-26-03 |
| eClass | 6 | 27-24-26-03 |
| ETIM | 10 | EC001598 |
| ETIM | 9 | EC001598 |
| ETIM | 8 | EC001598 |
| ETIM | 7 | EC001598 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

**Approvals / Certificates**

**General Product Approval**

Manufacturer Declaration

**General Product Approval** | **EMV** | **Maritime application**

**Maritime application**

NK / Nippon Kaiji Kyokai | CCS (China Classification Society) | KR (Korean Register of Shipping)


© Copyright Modulplc

**last modified:** 4/4/2025


Subject to change without notice
© Copyright Modulplc