



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; direct connection, integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

Input current			
from supply voltage 1L+, max.	16 A		
from load voltage 2L+ (without load), max.	16 A		
Accessories			
Function description	Terminal module direct: PROFIBUS DP and 24 V power; up to 6 x M20 cable glands		
belongs to product	ET 200pro; IM154-1/2 DP		
Dimensions			
Width	90 mm		
Height	130 mm		
Depth	100 mm		
Weights			
Weight, approx.	292 g		
Classifications			
		Version	Classification
	eClass	16	27-24-26-03
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Approvals / Certificates	
General Product Approval	

[Miscellaneous](#) [Manufacturer Declaration](#)



General Product Approval

Maritime application



[China RoHS](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

last modified:

4/7/2025