SIEMENS

Data sheet 6ES7421-1EL00-0AA0

SIMATIC S7-400, digital input SM 421, isolated 32 DI; 120 V DC/AC

Input current	
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	6.5 W
Digital inputs	
Number of digital inputs	32
Input characteristic according to IEC 61131	Type 1
Number of simultaneously controllable inputs	
● Number of simultaneously controllable inputs	32
Input voltage	
● Type of input voltage	AC/DC
● Rated value (UC)	120 V; 47 ... 63 Hz
● for signal "0"	0 to 20 V UC
● for signal "1"	79 to 132 V AC; 80 to 132 V DC
Input current	
● for signal "0", min.	0 mA
● for signal "0", max. (permissible quiescent current)	1 mA
● for signal "1", typ.	2 mA; 2 to 5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	5 ms
— at "0" to "1", max.	25 ms; 10 / 20 ms
— at "1" to "0", min.	5 ms
— at "1" to "0", max.	25 µs
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
Interrupts/diagnostics/status information	
Diagnostics indication LED	
● Status indicator digital input (green)	Yes
Potential separation	
Potential separation digital inputs	
● between the channels	Yes
● between the channels, in groups of	8
● between the channels and backplane bus	Yes

© Copyright Modulplc

Isolation	
Isolation tested with	1 500 V AC
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	600 g

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

General Product Approval | **EMV** | **For use in hazardous locations**

China RoHS | Miscellaneous | Manufacturer Declaration | FM

For use in hazardous locations | **Maritime application**

NK / Nippon Kaiji Kyokai

Maritime application

CCS (China Classification Society)

last modified: 6/7/2025

© Copyright Modulplc

© Copyright Modulplc