

SIMATIC IPC227G 2x display ports; 3x 10/100/1000 Mbps Ethernet; 4x USB3.0, 2x M.2 expansion slot; 24 V DC industrial power supply Atom X6413E (2-core); 4 GB RAM / with USB flash drive (documentation) without COM; without mass storage; NVRAM; without software; mounting onto standard rail;

General information	
Product type designation	IPC227G
Installation type/mounting	
Mounting	DIN rail mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Input current	
Current consumption (rated value)	0.7 A
Current consumption, max.	1.9 A
Inrush current, max.	2.5 A
Processor	
Processor type	Intel Atom X6413E
Chipset	SoC
Graphic	
Graphics controller	Integrated
Drives	
SSD	Yes; 256 Eco
Storage	
Type of memory	DDR4 SO-DIMM
Main memory	8 GB RAM
Capacity of main memory, max.	16 Gbyte
Interfaces	
Number of industrial Ethernet interfaces	3; 3x Ethernet (RJ45)
Video interfaces	
• Graphics interface	2x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Protocols	
Protocols (Ethernet)	
• TCP/IP	Yes
Interrupts/diagnostics/status information	
LED status display	1x power, 3x user
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Fan	No
• Monitoring function via network	Optional
Degree and class of protection	
IP degree of protection	IP40
Standards, approvals, certificates	
CE mark	Yes

UKCA mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
BSMI	Yes
BIS	Yes
Dust protection	Protection against foreign bodies > 1 mm
Marine approval	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Korean Register of Shipping (KRS)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (Class NK)	Yes
• Chinese Classification Society (CCS)	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Operating systems	
without operating system	Yes
pre-installed operating system	
• Windows 10	Yes; Windows 10 IoT Enterprise 2019 LTSC, 64 bit, MUI
Dimensions	
Width	191 mm
Height	100 mm
Depth	64 mm
Approvals / Certificates	
General Product Approval	
Manufacturer Declaration	 
Miscellaneous	 
General Product Approval	
	BIS CRS 
China RoHS	 
Maritime application	
	NK / Nippon Kaiji Kyokai CCS (China Classification Society)
	KR (Korean Register of Shipping) Test Summary Report UN 38.3
Dangerous goods	
Environment	



last modified:

5/24/2026 