



Figure similar

*** spare part *** SIMATIC DP, Power Rail Booster Signal amplifier for the transfer of the PROFIBUS DP via sliding contacts max. 500 Kbit/s

Supply voltage			
permissible range, lower limit (DC)	20.4 V		
permissible range, upper limit (DC)	28.8 V		
Input current			
Current consumption, max.	1.2 A		
Power loss			
Power loss, max.	20 W		
Degree and class of protection			
IP degree of protection	IP20		
Dimensions			
Width	90 mm		
Height	132 mm		
Depth	67.5 mm		
Classifications			
		Version	Classification
	eClass	16	27-24-26-08
	eClass	14	27-24-26-08
	eClass	12	27-24-26-08
	eClass	9.1	27-24-26-08
	eClass	9	27-24-26-08
	eClass	8	27-24-26-08
	eClass	7.1	27-24-26-08
	eClass	6	27-24-26-08
	ETIM	10	EC001604
	ETIM	9	EC001604
	ETIM	8	EC001604
	ETIM	7	EC001604
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			

[Miscellaneous](#)



[Manufacturer Declaration](#)



[China RoHS](#)

[Manufacturer Declaration](#)

Maritime application



last modified:

8/22/2025