

Article No. : 6SL3210-1PE31-8UL0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



Figure similar


| Rated data                                                                                                                                                                    |                     |                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------|
| Input                                                                                                                                                                         |                     |                        |
| Number of phases                                                                                                                                                              | 3 AC                |                        |
| Line voltage                                                                                                                                                                  | 380 ... 480 V ±10 % |                        |
| Line frequency                                                                                                                                                                | 47 ... 63 Hz        |                        |
| Rated current (LO)                                                                                                                                                            | 172.00 A            |                        |
| Rated current (HO)                                                                                                                                                            | 154.00 A            |                        |
| Output                                                                                                                                                                        |                     |                        |
| Number of phases                                                                                                                                                              | 3 AC                |                        |
| Rated voltage                                                                                                                                                                 | 400V IEC            | 480V NEC <sup>1)</sup> |
| Rated power (LO)                                                                                                                                                              | 90.00 kW            | 125.00 hp              |
| Rated power (HO)                                                                                                                                                              | 75.00 kW            | 100.00 hp              |
| Rated current (LO)                                                                                                                                                            | 178.00 A            |                        |
| Rated current (HO)                                                                                                                                                            | 145.00 A            |                        |
| Max. output current                                                                                                                                                           | 290.00 A            |                        |
| Pulse frequency                                                                                                                                                               | 2 kHz               |                        |
| Output frequency for vector control                                                                                                                                           | 0 ... 200 Hz        |                        |
| Output frequency for V/f control                                                                                                                                              | 0 ... 550 Hz        |                        |
| Overload capability                                                                                                                                                           |                     |                        |
| Low Overload (LO)                                                                                                                                                             |                     |                        |
| 1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s<br>1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s   |                     |                        |
| High Overload (HO)                                                                                                                                                            |                     |                        |
| 1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s<br>2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s |                     |                        |
| General tech. specifications                                                                                                                                                  |                     |                        |
| Power factor λ                                                                                                                                                                | 0.95                |                        |
| Offset factor cos φ                                                                                                                                                           | 0.99                |                        |
| Efficiency η                                                                                                                                                                  | 0.98                |                        |
| Sound pressure level (1m)                                                                                                                                                     | 68 dB               |                        |
| Power loss                                                                                                                                                                    | 2.31 kW             |                        |
| Filter class (integrated)                                                                                                                                                     | -                   |                        |

| Ambient conditions             |                                            |
|--------------------------------|--------------------------------------------|
| Cooling                        | Internal air cooling                       |
| Cooling air requirement        | 0.153 m³/s (5.403 ft³/s)                   |
| Installation altitude          | 1,000 m (3,280.84 ft)                      |
| Ambient temperature            |                                            |
| Operation LO                   | -20 ... 40 °C (-4 ... 104 °F)              |
| Operation HO                   | -20 ... 50 °C (-4 ... 122 °F)              |
| Transport                      | -25 ... 55 °C (-13 ... 131 °F)             |
| Storage                        | -25 ... 55 °C (-13 ... 131 °F)             |
| Relative humidity              |                                            |
| Max. operation                 | 95 % RH, condensation not permitted        |
| Connections                    |                                            |
| Line side                      |                                            |
| Version                        | M10 bolt                                   |
| Conductor cross-section        | 35.00 ... 120.00 mm²<br>(AWG 2 ... AWG -3) |
| Motor end                      |                                            |
| Version                        | M10 bolt                                   |
| Conductor cross-section        | 35.00 ... 120.00 mm²<br>(AWG 2 ... AWG -3) |
| DC link (for braking resistor) |                                            |
| Version                        | Screw-type terminals                       |
| Conductor cross-section        | 25.00 ... 70.00 mm²<br>(AWG 4 ... AWG -1)  |
| Cable length                   | 10 m (32.81 ft)                            |
| PE connection                  | M10 screw studs                            |
| Max. motor cable length        |                                            |
| Shielded                       | 300 m (984.25 ft)                          |
| Unshielded                     | 450 m (1,476.38 ft)                        |
| Mechanical data                |                                            |
| Degree of protection           | IP20 / UL open type                        |
| Frame size                     | FSF                                        |
| Net weight                     | 57.00 kg (125.66 lb)                       |
| Dimensions                     |                                            |
| Width                          | 305 mm (12.01 in)                          |
| Height                         | 708 mm (27.87 in)                          |
| Depth                          | 357 mm (14.06 in)                          |
| Standards                      |                                            |
| Compliance with standards      | UL, cUL, CE, C-Tick (RCM), SEMI F47        |
| CE marking                     | Low-voltage directive 2006/95/EC           |

Data sheet for SINAMICS Power Module  
PM240-2

Article No. : 6SL3210-1PE31-8UL0

| Converter losses to IEC61800-9-2*                    |         |
|------------------------------------------------------|---------|
| Efficiency class                                     | IE2     |
| Comparison with the reference converter (90% / 100%) | 50.60 % |



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

\*calculated values

<sup>1)</sup>The output current and HP ratings are valid for the voltage range 440V-480V